

Accessories

Gotive H41 Travel Charger

Light-weight charging option for Gotive H41 (Model 5)

Light-weight portable charging solution

For any working conditions in which the Gotive H41 Docking Station (DS) or Gotive H41 Simple Docking Stations (SDS) might be "too bulky or too intelligent", the direct Gotive Travel Charger (TC) is the ideal space-friendly light-weight portable charging solution.

Charging without docking - indoor and in vehicle


Gotive Travel Charger consists of two parts - TC Plug designed to be clicked into the pin area on the back of the Gotive H41 Model 5 communicator, and the TC cable with power supply adaptor (220 V). The latter one can be exchanged for TC cable with CL Adapter for easy charging in the vehicle (12 V / 24 V).

Ergonomy sustained for daily work


Without the cable plugged in, the Travel Charger Plug is submerged into the body of the communicator and doesn't hinder any operation, handling, or wearing the unit in the carrying case. For charging, just plug in the TC cable.

Compatibility with other charging options


The TC Plug can also be easily removed from the communicator, in order to place the communicator into the other Gotive charging and docking stations. Gotive H41 handheld communicator Model 5 ("Travel Charger Ready") is compatible with all other docking and charging options of Gotive H41 Series - the Docking Station, Simple Docking Station and the Multi Docking Station.



Travel Charger plug doesn't hinder daily operation



Travel Charger plug doesn't hinder daily wearing



Easy charging via Travel Charger

Gotive H41 Travel Charger works only with Gotive H41 Series Model 5 and higher, and with H41SCR Smart Card Reader Device - it will neither charge nor hold in the preceding models of Gotive H41 communicators.



Click in the Travel Charger plug with the lock latch facing towards its counterpart



Plug in the power cable



Before docking the communicator into Gotive DS/SDS take out the TC plug by unlocking the latch

Physical Characteristics

TC Plug Dimensions	Length: 45 mm; Width: 14 mm; Height: 20 mm
	Length: 1.75 in; Width: 0.55 in; Height: 0.79 in

Weight	9 g
--------	-----

Power

Input	5 VDC $\pm 5\%$; max. 3 A
TC Power Supply Adapter + Cable	Input: 100/240 Vac, 50-60 Hz, Output: +5 V $\overline{\text{---}}$ 3 A
TC CL Adapter + cable	Input: 12/24 Vdc, 2.1 A, Output: +5 Vdc, 3.0 A, 15 W max